



Comparison

 www.rex-synfelt.com

REX™ SynFelt	30# Conventional Felt
100% Polypropylene	Asphalt
Most slip resistant in the industry due to a proprietary formulation and unique walking pattern	Hard to walk on without slipping
28 lbs per roll – 10x lighter per sq than 30# roofing felt	60 lbs per roll
10 squares per roll – 48” wide x 250 lineal feet	2 squares per roll – 36” wide x 72 lineal feet
20x stronger than felt. Highest cross directional tear resistance in the industry.	Easy to tear
Can be left exposed for up to 6 months with no degrading	Begins to degrade immediately
25 year warranty	No warranty
Lays flat and is water resistant. Superior drapability in valleys, on ridges and hips	Puckers & wrinkles when wet Cracks in valleys, on ridges and hips
Pre-printed nailing pattern and overlap lines to speed installation	No nailing pattern
Class A fire rating	No fire rating
Saves up to 50% time in labor installation	No comparison

Alpha ProTech Engineered Products Inc.
 301 South Blanchard St.
 Valdosta, GA 31601
 866-312-1837

Nationwide Distributions Centers
 Valdosta, Georgia
 Janesville, Wisconsin
 Nogales, Arizona
 Salt Lake City, Utah



SynFelt: Synthetic Roof Underlayment