

# REX™ SYN FELT

**REX™ Synfelt** is a high strength mechanically fastened roof underlayment that offers a Limited Lifetime warranty. Tailored for the most demanding projects, it can withstand exposure for 6 months without buckling or curling when damp. It's high-temp rating makes it an ideal choice for any project.

## PRODUCT SPECIFICATIONS

Roll Size	10SQ	5SQ
Length	250'	125'
Width	48"	48"
Rolls/Pallet	35	54
Pallets/Truck	45	55
Rolls/Truck	1,575	2,970
UV Exposure	6 Months	
Warranty	Limited Lifetime	



## TECHNICAL SPECIFICATIONS

Test	Method	Result
Tensile Strength	ASTM D5034	92 / 121 MD / CD
Hydrostatic Resistance	ASTM D8257	Pass
Thermal Cycling	ASTM D8257	Pass
Accelerated Weathering	ASTM D8257	Pass
Faster Pull-Through Resistance	ASTM D8257	Pass
Pliability	ASTM D8257	Pass
Unrolling	ASTM D8257	Pass
Liquid Water Transmission	ASTM D8257	Pass
Tear Resistance	ASTM D8257	Pass
Linear Dimensional Change	ASTM D8257	Pass
Moisture Vapor Performance	ASTM D8257	Pass
Burst Strength	ASTM D8257	Pass
Fire Classification	ASTM E108	Class A

## CODE APPROVALS

ASTM D226 Types I & II	Yes
ASTM D8257	Yes
Class A Fire (As part of a system)	Yes
Texas Department of Insurance	Yes
Florida Product Approval	FL12512
Miami Dade County Approved	Yes
Code Listed	ESR-1601
Contributes to LEED points	Yes
Approved for High-Temp Installation	Yes

<b>Custom Logo Requirements</b>	1 Color	2 Pallets
	2 & 3 Colors	6 Pallets